


L-C20 Pro

ECR Terminal



**Elevate user experience to
new heights with futuristic terminal.**

- Enhance user perception with interactive design.
- Tackle peak hours with seamless and speedy printing.
- Empowered by LANDI Connect platform to unlock the full potential of digital commerce.



SPECIFICATIONS

Processor	Qualcomm Octa-core, up to 2.4GHz	Size	23.5cm x 36cm x 36cm 9.25" x 14.17" x 14.17"
OS	Android 13 GMS	Connectivity	Wi-Fi: IEEE802.11 a/b/g/n/ac 2.4G and 5G ETH: 1000M Bluetooth 5.0, support BLE Optional, 4G fallback 3G and GPRS
Memory	Internal: 4GB RAM+64GB FLASH 8GB RAM+128GB FLASH (Optional) External: Micro SD Card (Up to 2TB)		Positioning
Main display	15.6",1920x1080,FHD capacitive multi-touch	Audio	Speaker: 5W, 100dB@1m, Dual Speaker Headset: 3.5mm audio jack MIC: Dual Microphone
Customer display	Optional 1:None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3: 10.1"Premium CFD (1280x800,Touch panel, QR Camera, NFC)	Camera (Optional)	Optional 1: None Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1" Premium CFD) Optional 3: Facial recognition ability camera (USB device, plug into Main display edge expansion port)
Printer	80mmThermal Printer, Diameter:80mm Print speed:200mm/s, Auto Cutter	NFC	Android NFC, ISO / IEC 14443、ISO15693 compliant, support Type A / B, Mifare, Felica (Only supported on the 10.1" Premium CFD)
Ports	1 USB Type-C, debug port, 4 USB Type-A 2.0+1 USB Type-A 3.0 1 RJ22 Serial port, 1 RJ45 Ethernet port, 1 RJ11 Cash drawer port 1 3.5mm Audio port, 1 MicroSD slot 1 Power port	SAM/SIM slots	1 SIM (Optional)
		PSU	19~20V/3.25A
Buttons	1 Power key with indicator light (Red&blue) 2 Volume keys 1 Function key	Environment	Operating temperature : 0℃ to +40℃ Storage temperature : -20℃ to +60℃ Operating humidity: 10% to 90% non-condensing
		Certification	CE/CB/FCC/IC/RoHS/WEEE

This document is not binding and the specifications above may be modified without prior notification.